

STRAP

For Hawle pipe saddles for steel, cast iron and asbestos cement pipes



Design features

No. 3111

- Including ball discs and nuts
- Max. tightening torque 100 Nm
- Made of stainless steel, passivated
- Rubber cover made of elastomer



Dimension DN	Suitable for pipe type			Markings					
	Steel	Cast iron	AZ	Ø-Diameter range of strap	Control dimension „L”	DN	Pipe type		
*50				60 - 70	344	50	ST	G	AZ
*65				70 - 82	374	65	ST	G	AZ
*80				89 - 108	410	80	ST	G	AZ
*100				102 - 130	455	100	ST	G	AZ
*125				132 - 158	520	125	ST	G	AZ
*150				159 - 185	595	150	ST	G	AZ
175				185 - 210	685	175	ST	G	
200				210 - 235	760	200	ST	G	
*200				219 - 244	785	200		G	AZ
*250				264 - 288	905	250	ST	G	
250				288 - 310	975	250			AZ
*300				316 - 340	1055	300	ST	G	
300				335 - 360	1130	300			AZ
*350				355 - 380	1155	350	ST	G	
350				390 - 410	1250	350			AZ
400				406 - 429	1300	400	ST		
*400				415 - 440	1325	400	ST	G	
400				450 - 475	1425	400			AZ
*450				467 - 485	1480	400	ST	G	
450				496 - 520	1570	450			AZ
*500				518 - 535	1630	450	ST	G	
500				578 - 600	1810	500			AZ
*600				620 - 640	1945	600	ST	G	
600				680 - 700	2120	600			AZ

* When ordering without reference to the pipe type or without information on the external Ø, the saddle clamps will be delivered with a strap for this labelled Ø range